



| Type                             | BOB12-14-8040-TD                         |
|----------------------------------|--|
| Order No                         | BOB12-14-8040-TD                         |
| Lamp type/assembly               | Standing luminaire                       |
| Colour                           | White                                    |
| Light source                     | LED                                      |
| Energy efficiency class          | LED                                      |
| Colour temperature               | 4000K                                    |
| Colour rendering index           | CRI > 80                                 |
| Operating mode                   | Touchdim                                 |
| Operation                        | On tube                                  |
| Base                             | U-base                                   |
| Finish                           | Matt, structured                         |
| Power cable                      | Black, 3x0.75mm <sup>2</sup> , L 3000 mm |
| Mains plug                       | Swiss plug type J                        |
| Light distribution               | Direct (16%) / indirect (84%)            |
| UGR                              | < 8.2                                    |
| Total luminous flux of luminaire | 10215lm @ 4000K                          |
| Power consumption                | 74W                                      |
| Luminaire efficacy               | 139 lm/W                                 |
| Safety class                     | I  |
| Protection type                  | IP20                                     |
| Packaging units                  | 3  |
| Weight                           | 16kg                                     |
| Guarantee                        | 36 months                                |

**Belux AG**

Neufeldweg 6, CH-5103  
Möriken  
Tel. +41 61 316 74 01  
Fax +41 61 316 75 99  
www.belux.com  
belux@belux.com

